



Salvi

Light inspired by you

Baliza Nova M



Baliza Nova M

Triangular beacon with curved sides composed of slats joined together, protecting the optical group from vandalism.

Ideal for lighting paths in residential areas, pedestrian zones.

Technical characteristics

Height 60 cm light point	Dimensions Ø332 × 600 mm	Maximum power Maximum power 33W
Peak flow Maximum flux 9180lm.	Weight approx. Approximate weight: 9kg.	IP / IK IP65 / IK09
Colour temperature 3000°K or 4000°K. Optionally available for environmentally friendly areas: amber filter, 2200°K or 2700°K.	FHS < 0,1%	CRI Minimum 70
Lifespan L90B10 > 100,000 h (consult according to LED type and configuration).	Voltage AC 220 V - 240 V ~ 50/60 Hz *Class I / Class II optional.	Color Sand Brown M2. Other colors available.
Composition Body in cast aluminium (E N1706 43000)	Fixing Fixing with bolts on Ø266 mm base.	Closing/opening Access to the equipment through the front cover, fixed to the body with M6 captive screws
Diffuser Transparent or frosted injected polycarbonate diffuser in the shape of a bucket.	LED system Includes 3 modules with 9 high-efficiency LEDs. Ask about other options.	

Lenses
Standard IEC 60598, IEC 62031, IEC 62471, IEC 60529, EN 55015, IEC 61000, IEC 61547, IEC 62493, IEC 62471, IEC 61437, IEC 62384, EN 50102, CE.

ISO ISO 9001, ISO 14001, ISO 45001.

Proportions

The technical drawings illustrate the proportions of the luminaire. The top view shows a bucket-shaped diffuser with a width of 305 mm. The side view shows a diameter of 332 mm and a height of 186 mm. The front view shows a height of 650 mm for the main body, with a series of horizontal slats for the light distribution.

Photometries / Versions

nan

nan

nan

Please refer to the product configurator for other options.

Versions

PCB	mA	2700K			3000K	
		W	lm	lm/W	lm	lm/W
36Z	300	33	5760	174	6120	185
	300	33	5760	174	6120	185
	300	33	5760	174	6120	185
54Z	200	33	8640	261	9180	278
	200	33	8640	261	9180	278
	200	33	8640	261	9180	278

Avda. del Vallés, 36 - 08185
Lliçà de Vall - Barcelona, Spain
www.salvi.es

Light inspired by you
info@salvi.es
+34 938 445 190

Salvi

2025-01 / Due to constant technological evolution, SALVI reserves the right to modify specifications without prior notice. The information contained in this document is for guidance only and does not constitute a contractual commitment.

