



Salvi

Light inspired by you

Baliza Nova S



Baliza Nova S

Triangular beacon with curved sides composed of slats joined together, protecting the optical group from vandalism.

Ideal for lighting paths in residential areas, pedestrian zones.

Technical characteristics

Height

40 cm light spot

Dimensions

Ø240 × 400 mm

Maximum power

Maximum power 39W

Peak flow

Maximum flux 5580lm.

Weight approx.

Approximate weight: 7Kg.

IP / IK

IP65 / IK09

Colour temperature

3000°K or 4000°K. Optionally available for environmentally friendly areas: amber filter, 2200°K or 2700°K.

FHS

< 0,1%

CRI

Minimum 70

Lifespan

L90B10 > 100,000 h (consult according to LED type and configuration).

Voltage

AC 220 V - 240 V ~ 50/60 Hz

*Class I / Class II optional.

Color

Sand Brown M2. Other colors available.

Composition

Body in cast aluminium (E N1706 43000)

Fixing

Fixing with bolts on Ø173 mm base.

Closing/opening



Access to the equipment through the front cover, fixed to the body with M6 captive screws.

Diffuser

Transparent or frosted injected polycarbonate diffuser in the shape of a bucket.

LED system

Includes two modules with nine high-efficiency LEDs. Ask about other options.

Lenses**Proportions**

Standard

IEC 60598, IEC 62031, IEC 62471, IEC 60529, EN 55015, IEC 61000, IEC 61547, IEC 62493, IEC 62471, IEC 61437, IEC 62384, EN 50102, CE.

ISO

ISO 9001, ISO 14001, ISO 45001.

Photometries / Versions

nan

nan

nan

Please refer to the product configurator for other options.

Versions

PCB	mA	2700K			3000K	
		W	lm	lm/W	lm	lm/W
18D	350	20	2880	144	3060	153
	500	28	3960	141	4140	147
	700	39	5400	138	5580	143
18C	350	20	2880	144	3060	153
	500	28	3960	141	4140	147
	700	39	5400	138	5580	143

Avda. del Vallés, 36 - 08185
Lliçà de Vall - Barcelona, Spain
www.salvi.es

Light inspired by you
info@salvi.es
+34 938 445 190

Salvi

2025-01 / Due to constant technological evolution, SALVI reserves the right to modify specifications without prior notice. The information contained in this document is for guidance only and does not constitute a contractual commitment.

